



FLOWSERVE[®]

Norbro
J Switch

Standard Product Code



For alternatives please contact technical sales.

Switch Code	Switch Type	Manufacturer Reference	ATEX Approved	Switch Certification
P&F	Inductive Sensor	Pepperl & Fuchs NJ2-V3-N	Yes	EEx ia
X23	SPDT Explosion Proof	Honeywell 91SE1-3	Yes	Ex N/d
X26	SPDT Gold Contact Explosion Proof	Honeywell 91SE1-3N55	Yes	Ex N/d
X29	SPDT Silver Contact	Burgess XGG3-88Z1	No	
X65	SPDT Silver Contact	Burgess XGG3-88Z1	Yes *	
X66	SPDT Explosion Proof	Burgess E1V3C-ATEX	Yes	EEx d

* When used through a barrier (10V, 14MA, 35mW max.) the X65 is certified to EEx ia.

Cable Entry	Specification
J1	Pg 16
J2	20mm Plain Hole
J3	Pg 13.5
J4	M20 x 1.5p

- Guaranteed operation directly off support rods
- Factory assembled and tested actuator/J Switch package option
- IP66 rated enclosure
- Direct Mounting (no bracketry)
- Robust Metal Construction
- Proven Norbro quality and reliability
- Enclosure IIGDc Rated

